


BUTT AND PARALLEL CONNECTORS



butt connectors

PVC insulated



parallel connectors

Cond. Size sqmm (AWG)	Ref.	Ø mm	L mm	Quantity Box/Bag
0,2-0,5 (24-20)	PL 01-M	3,0	25	3.000/100
0,25-1,5 (22-16)	PL 03-M	4,0	25	2.000/100
1,5-2,5 (16-14)	PL 06-M	5,0	25	1.500/100
4-6 (12-10)	PL 1-M	6,5	32	800/100
0,25-1,5 (22-16)	PL 03-P	4,0	20	3.000/100
1,5-2,5 (16-14)	PL 06-P	5,0	16	2.000/100

PL-M PL-P




Manufactured from copper tube
 - Electrolytically tin plated
 - Recommended crimping tools are shown on pages 84 to 91

BUTT CONNECTORS



Nylon insulated



Cond. Size sqmm (AWG)	Ref.	Ø _i mm	L mm	Quantity Box/Bag
0,25-1,5 (22-16)	NL 03-M	4,0	25,0	2.500/100
1,5-2,5 (16-14)	NL 06-M	5,4	25,5	1.500/100
4-6 (12-10)	NL 1-M	5,4	32,0	1.000/100
10 (8-7)	NL 2-M	6,8	43,0	500/100
16 (6-5)	NL 3-M	7,9	44,0	500/100

NL-M




Manufactured from copper tube
 - Electrolytically tin plated
 - Recommended crimping tools are shown on pages 84 to 91

CLOSE END CONNECTORS



Nylon insulated



Cond. Size sqmm (AWG)	Ref.	Ø _i mm	L mm	Quantity Box/Bag
1,5-2,5 (16-14)	NL 06-P	7,9	19,9	1.500/100
	NL 06-PB	6,5	13,6	1.500/100
4-6 (12-10)	NL 1-P	10,5	21,5	800/100
	NL 1-PG	9,0	17,8	1.000/100

NL-P



Manufactured from copper tube
 - Electrolytically tin plated
 - Recommended crimping tools are shown on pages 84 to 91